




Bit Size Range	5- ⁵ / ₈ - 6- ³ / ₄ in	143 - 171 mm
Bit Box Connection	3- ¹ / ₂ REGULAR	
Dynamic Bearing Load On/Off Bottom	71500 lbf	31800 daN
Static Bearing Load On/Off Bottom	229350 lbf	102000 daN
Max. Overpull (For Re-run)	328000 lbf	145900 daN
Absolute Overpull	546000 lbf	242900 daN
Adjustable Makeup Torque	12000 ft-lbs	16300 Nm
Stab/Thread Protector Makeup Torque	8000 ft-lbs	10800 Nm
A = Bit to Stabilizer (Centre)	16.7 in	424 mm
B = Bit to Bend	Adjustable 56.3 in	1430 mm
	Fixed 45.7 in	1161 mm
C = Overall (With Dump Sub)	295.5 in	7506 mm
Weight	1156 lbs	524 kg

Lobe Configuration	7-8 Lobe 3.8 Stage HR	
Displacement (No Load)	0.54 rev/gal	0.14 rev/l
Max. Differential (Full Load)	900 psi	6205 kPa
Max. Torque	4130 ft-lbs	5600 Nm
Max. Power	90 HP	67 kW

Flow Rate		Speed
GPM	LPM	RPM
100	379	35 - 50
175	662	75 - 95
250	946	115 - 140



Possible damage may occur when motor is run higher than 70% of Maximum Differential Pressure.

ADJUSTABLE BUILD RATE

Hole Size	SLICK				STABILIZED			
	5- ⁷ / ₈ (149mm)	6 (152mm)	6- ¹ / ₈ (156mm)	6- ¹ / ₄ (159mm)	5- ⁷ / ₈ (149mm)	6 (152mm)	6- ¹ / ₈ (156mm)	6- ¹ / ₄ (159mm)
BEND ANGLE	Degrees per 100 Feet (30m)				Degrees per 100 Feet (30m)			
0.39	3.3	2.9	2.4	1.9	3.3	2.9	2.6	2.7
0.78	6.7	6.2	5.8	5.3	6.7	6.2	5.8	5.6
1.15	9.9	9.5	9.0	8.5	9.9	9.5	9.0	8.5
1.50	13.0	12.5	12.0	11.5	13.0	12.5	12.0	11.5
1.83	15.8	15.4	14.9	14.4	15.8	15.4	14.9	14.4
2.12	18.4	17.9	17.4	16.9	18.4	17.9	17.4	16.9
2.38	20.6	20.1	19.6	19.2	20.6	20.1	19.6	19.2
2.60	22.5	22.0	21.6	21.1	22.5	22.0	21.6	21.1
2.77	24.0	23.5	23.0	22.6	24.0	23.5	23.0	22.6
2.90	25.1	24.6	24.2	23.7	25.1	24.6	24.2	23.7
2.97	25.7	25.3	24.8	24.3	25.7	25.3	24.8	24.3
3.00	26.0	25.5	25.0	24.5	26.0	25.5	25.0	24.5

Note: Stabilizers are 1/8" undergauge

FBH BUILD RATE

Hole Size	SLICK				STABILIZED			
	5- ⁷ / ₈ (149mm)	6 (152mm)	6- ¹ / ₈ (156mm)	6- ¹ / ₄ (159mm)	5- ⁷ / ₈ (149mm)	6 (152mm)	6- ¹ / ₈ (156mm)	6- ¹ / ₄ (159mm)
BEND ANGLE	Degrees per 100 Feet (30m)				Degrees per 100 Feet (30m)			
1.25	10.6	10.0	9.5	8.9	10.6	10.0	9.5	9.5
1.50	12.8	12.2	11.6	11.0	12.8	12.2	11.6	11.4
1.75	14.9	14.4	13.8	13.2	14.9	14.4	13.8	13.3
2.00	17.1	16.5	16.0	15.4	17.1	16.5	16.0	15.4
2.25	19.3	18.7	18.1	17.6	19.3	18.7	18.1	17.6
2.50	21.5	20.9	20.3	19.7	21.5	20.9	20.3	19.7

This information is for reference only. Build rates are theoretical calculations using three-point geometry and new motor builds. Actual rate predictions will depend on formation characteristics, bit profiles, and WOB.

For custom motor configurations and build rates, please contact your DYNOMAX office.